



Horizontal braces

✓ Professional use

- Available in three widths (1.85, 2.45 and 3.05 metres)
- Suitable for the RS4 and RS5



Altrex horizontal braces: Uniquely coated pawls make them recognisable.

You erect your rolling tower safely up to any required height using Altrex horizontal braces. The horizontal braces are available in the dimensions of 1.85, 2.45 and 3.05 metres. The braces are designed in such a way that they include a claw & brace-pipe connection. Thanks to this connection, the brace-pipes are stronger and extra safe. To avoid confusion, the horizontal braces are uncoated.



Squeezed claw & brace-pipe connection

The horizontal braces are designed in such a way that they include a claw & brace-pipe connection. Thanks to this connection, the brace-pipes are stronger and extra safe.



Coloured pawls

The horizontal braces of the RS TOWER 5 come with red pawls for easy recognition. The horizontal braces of the RS TOWER 4 series are uncoated.



Sturdy protection bumper

The sturdy protection bumper guarantees the firmness of the claws. This protection bumper ensures that the claw is always secured. The result is that the claw can take some knocks and that dirt is not a problem.

Product specifications

Item number	EAN	Description	length	series
303704	8711563133365	Horizontal brace 185 RS TOWER 5	185	RS TOWER 5
303706	8711563133372	Horizontal brace 245 RS TOWER 5	245	RS TOWER 5
303708	8711563133389	Horizontal brace 305 RS TOWER 5	305	RS TOWER 5
304304	8711563131248	Horizontal brace 185 RS TOWER 4	185	RS TOWER 4
304306	8711563131262	Horizontal brace 245 RS TOWER 4	245	RS TOWER 4